



5700®

RIDE-ON SCRAPER

5700-AKT, 5700-AUS, 5700-BOL, 5700-EUR, 5700-HER, 5700-JPN, 5700-KAN, 5700-KTU, 5700-UK, 5700-SUN, 5700DL-HER, 5700DL, 5700HS, 5700-LIN



5700HS: Designed to cover more space in less time; specifications made to order.
Special Note: the 5700 can be ordered with lifting arms, to make jobsite maneuvering easier.

5700 Specifications

Power Supply	Battery	
Width*	24.5"	62 cm
Height	50"	127 cm
Length*	58"	147.32 cm
Weight	2,244 lb	1,017.9 kg
Removable Weight	185 lb front	83.9 kg front
Weight (machine only)	2,059 lb	933.9 kg
Speed	Up to 120 ft/min 160 ft/min for HS	up to 36.6 m/min 48.8 m/min for HS
Voltage	115	230
Frequency	60 Hz	50 Hz

5700DL Specifications

Power Supply	Battery	
Width*	24.5"	62 cm
Height	50"	127 cm
Length*	63"	160 cm
Weight	2,407 lb	1,091 kg
Removable Weight	185 lb front	84 kg front
Weight (machine only)	2,222 lb	1,007 kg
Speed	up to 120 ft/min	up to 36.6 m/min
Voltage	115	230
Frequency	60 Hz	50 Hz

**Measurements are without tooling attached.
Meets the requirements of the Machine Directive 2006/42/EC and EMC Directive 2004/108/EC. It is CE marked.*

5700 is available with or without the Dual Lift. The Dual Lift feature adds operator controls for adjusting blade pitch and angle while remaining seated.

SAFETY

- A.** Automatic kill switch is triggered when the operator seat is vacant
- B.** Larger/deepened forklift pockets
- C.** E-stop knob for safety
- D.** Debris deflector protects machine from loose material

COMFORT

- E.** Ergonomic design includes movable foot pegs, taller handles, and an adjustable seat
- F.** Hinged hood system for easy access maintenance

PERFORMANCE

- G.** Precise hydraulic steering for maneuvering in tight spaces, zero turn radius
- H.** Quick-change swivel head blade holder
- I.** Optional dual-lift, hydraulic slide plate adjusts blade pitch and angle for continuous contact with the floor
- J.** Nonmarking tires
- K.** Twelve AGM 180-amp hour batteries provide 100 percent power, speed, and torque for 90 percent of the batteries' run cycle
- L.** Compact design fits through standard door frames and elevator doors
- M.** Front caster wheels allow increased maneuverability in tight spaces
- N.** LED light for increased visibility

INCLUDED WITH THE 5700

- 5110-100: Transport Wheels
- 402929: 3/4 x 1-1/8 Wrench
- 73507-1: 7 ft extension cord
- Operating and Service Manuals

- Kit 5175 includes:
 - 6277-BU: 45 degree, 3" x 12" self-scoring, bevel up
 - 6284: 3" x 12" heavy-duty blade
 - 6285: 3" x 6" heavy-duty blade
 - 6286: 3" x 12" heavy-duty blade

- 7050-12: 12" cutting head
- 7050-6: 6" cutting head
- 7079-2: 2" x 6" angle shank w/ carbide tip
- One-year manufacturer's warranty on parts and labor