

BEF 200N

SCARIFIER



HIGH PRODUCTION & RIGID DESIGN

FEATURES

- Rigid, compact design
- Quick Lift - Pulls Cutters In/Out of Cut
- 50mm dust extraction port
- Dust free when operated with a suitable vacuum
- Large diameter wheels for excellent mobility and stability
- Welded construction is rigid, strong and lower control
- Fine Adjust- Screw type raise and lower control
- Firm engine mounting plate
- Front wheels protected from debris
- Height adjustment at the handle

APPLICATIONS

- Cleaning and texturing concrete and asphalt
- Removal of paint, rust, grease, ice deposits, line markings, and concrete laitance
- Concrete reduction and scabbling
- Removal of roof chippings
- Grooving applications
- Cleaning concrete formwork and shuttering
- Non-slip finishes
- Removal of concrete and plaster droppings

TECHNICAL SPECS

| Type | Electric (1 Phase) | Electric (1 Phase) | Electric (3 Phase) | Gas / Petrol |
|----------------------------|--------------------|--------------------|--------------------|--|
| Part Number | BEF 200N-1 | BEF 200N-2 (A) | BEF 200N-3 | BEF 200N-4(A) |
| Power Output | 3hp / 2.2kW | 3HP / 2.2kW | 3hp / 2.2kW | (Gross) 5.5hp/4kW (Net) 4.8hp/3.6kW |
| Voltage | 110V | 230V | - | - |
| Cutter Head Speed | 1738 RPM | 1738 (2090) | 1738 RPM | 1833 RPM |
| Length | 990mm (39") | 990mm (39") | 990mm (39") | 990mm (39") |
| Width (Body) | 375mm (15") | 375mm(15") | 375mm (15") | 360mm (14") |
| Width (INCL. Handle) | 429mm (16") | 429mm (16") | 429mm (16") | 429mm (16") |
| Height | 942mm (37") | 942mm (37") | 942mm (37") | 942mm (37") |
| Weight | 62kg (137lbs) | 62kg (137lbs) | 62kg (137lbs) | 58kg (127lbs) |
| Working Width | 200mm (7,9") | 200mm (7,9") | 200mm (7,9") | 200mm (7,9") |
| Working Distance from Wall | 60mm (2.4") | 60mm (2.4") | 60mm (2.4") | 50mm (1.9") |
| Engine RPM | - | - | - | 3000 RPM |
| Motor RPM | 2870 RPM | 2870 (3450) | 2870 RPM | - |



BEF 200N



BEF 275



BEF 320