



SPRAYER S201 / S151



Ideal for spraying all types of curing compounds after finish work is completed.

- The best pump in the industry.
- Sprays materials with a variable pressure between 40 and 120 psi while constantly agitating material.
- Easily handles form oils, pigmented curing compounds, bond breakers, soaps and detergents, pest control liquids, and most liquid type material.
- Handles white pigment curing compounds up to 40% solids. (S201)
- S151 can handle up to 20% solids
- Designed to be used from a truck, dock, work platform, dolly or skid.
- Exclusive wear adjustment feature increases pump life as much as 200% (S201)
- Powered by dependable Honda engines.
- Comes with 25' (7.6m) of 3/8" (0.95cm) hose and adjustable spray nozzle that can be disassembled for easy cleaning. Barrel not included.

Options

- Hose Lengths: 50' (15.2m), 75' (22.7m) or 100' (30.5m)
- Fan Spray Nozzle
- Shown with hand cart
- Tow Cart



Specification S201 & S151	
Pressure	Between 40 and 120 psi
Engine	GX120
Hose Length Options	25' (7.6m), 50' (15.2m), 75' (22.8m)
Flow Rate	8gal/minute (30L/min)
Shipping Weight	120lbs (55kg)
Max Solids	S151 20% S201 40%

Additional information on accessories and consumables for our Sprayers is available through our website, or contacting us directly.



1-866-501-1683
375 Annagem Blvd. Mississauga,
ON, Canada, L5T 3A7
www.bartellmorrison.com



1-888-999-1570
200 Commerce Dr. Freehold,
NJ, U.S.A, 07728
www.bartellmorrison.com



44-(0)1673-860709
Honeyholes Lane, Dunholme
Lincoln. LN2 3SU. U.K.
www.spe-int.com



1-800-267-6682
832 80th St. SW. Everett,
Washington, U.S.A, 98203
www.innovatechproducts.com