

Hole Digging Equipment Hand Held



FEATURES

- Power-GRIP™ operator handle
- Auger-LOK™ for stuck auger removal
- Honda GX35 all-position engine
- All metal centrifugal clutch
- Precision, spur gear transmission
- 1 inch diameter auger drive connection
- Magura® twist grip throttle control

242H EPIC™ SERIES ONE MAN HOLE DIGGER

The 242H EPIC™ Series hand-held Hole Digger features an all position, 4 Stroke engine. No more mixing oil with gas. No more separate fuel cans. And, no more smoky, exhaust with a Honda engine that meets current EPA emission standards. The 242H is built with professional features that make it ideal for both contractors and homeowners alike. Performance to dig up to an 8 inch (203 mm) diameter hole in a variety of soil classifications. Built with oversized ball bearings, heat treated shafts and precise, machine-cut gears designed to deliver long service life and high ROI. The unique, ergonomically engineered Power-GRIP™ operator handle helps maximize control, strength and balance plus, dampens vibration and reduces the effects of kickback and body fatigue while increasing overall digging comfort, productivity and jobsite safety. The 242H is also equipped with the convenient Auger-LOK™ for removing stuck augers. For use with the 2350 Series earth augers and auger extension.

SPECIFICATIONS

Engine	1.3 HP (1000 W) Honda GX35, all-position, 4 Stroke
Starter	Hand rewind
Fuel	Gasoline, unleaded, automotive grade
Transmission	Totally enclosed, spur gear, grease lubricated
Maximum Digging Torque	51 ft lbs (64 N.m)
Nominal Auger Rotation Speed	166 RPM, no load
Auger Drive Connection	1 inch (25.4 mm) round
Available Auger Diameter Range	2 inch (51 mm) to 8 inch (203 mm)
Standard Auger Digging Length	30 inch (762 mm)
Available Auger Extension	15 inch (381 mm), plain-tube type
Weight (less auger)	28 lbs (13 kg)



All specifications are general in nature and are not intended for specific application purposes. General Equipment Company reserves the right to make changes in design, engineering, or specifications and to add improvements or discontinue manufacture at any time without notice or obligation. Consult applicable Operator Manual before utilizing. Refer to OSHA 2207 and/or current revisions for specific safety information. Names depicted are the registered trademarks of their respective owners.

Form: GEF10121901_v1.0