

## For Larger Mixing Jobs



### Mixer EHR 20.1 R Set

*The standard mixer with high reliability for construction*

Ideal for medium- to high-viscosity powder and liquid materials such as finished plaster, latex, mortar, epoxy, self-leveling compounds and other materials in batches up to 120 pounds.

Capacity: 3 bags, 25 gal.  
Output: up to 900 lbs./hour  
Power: 10.5 Amp / 110 Volt AC  
Free Speed: 900 RPM  
Load Speed: 250-580 RPM  
Weight: 11.5 lbs.  
Included Paddle: MG 140

Suitable Paddles:  
WG 135 (5.4" dia.)  
MG 140 (5.6" dia.)  
TWP 140 (5.5" dia.)



### Mixer EHR 23/1.3 R Set

*The powerful mixing drill for tough, continuous use*

A powerful 14.5 Amp motor allows mixing of up to 200 pounds of high-viscosity materials ranging from epoxy, mortars, plasters and cement to quartz-containing resins and flooring compounds, as well as insulation and other materials.

Capacity: 5 bags, 35 gal.  
Output: up to 1800 lbs./hour  
Power: 14.5 Amp / 110 Volt AC  
Free Speed: 150-325 RPM  
Load Speed: 100-275 RPM  
Weight: 15 lbs.  
Included Paddle: MG 160

Suitable Paddles:  
WG 160 (6.25" dia.)  
MG 160 (6.25" dia.)  
TWP 160 (6.375" dia.)



### Also available: Mixer EHR 23/2.4 S Set

*With 2-speed gearbox*

Load Speed: 0-250 / 0-580 RPM

**See the next page for our full line of heavy-duty galvanized steel mixing paddles and portable mixing stands.**

## Twin Paddle Mixing Save Time Mixing 2+ Component Materials



### Mixer EZR 22 R/RL Set

*Push-pull Mixer: Quick, thorough mixing with twin paddles and clockwise/ counterclockwise rotation*

This dual-paddle mixer with selectable clockwise and counterclockwise paddle rotation thoroughly mixes a wide variety of materials. The blades rotate in opposite directions, eliminating counter torque and making the unit easy to handle – even while mixing the most demanding of materials. Each paddle is 4<sup>3</sup>/<sub>4</sub>" dia. with 8<sup>1</sup>/<sub>4</sub>" working width. Mix up to 200 pounds. Use hand-held or mount on RST 91 stand.

Capacity: 5 bags, 25 gal.  
Output: up to 1200 lbs./hour  
Power: 10.5 Amp / 110 Volt AC  
Free Speed: 680 RPM


Load Speed: 0-450 RPM  
Weight: 15 lbs.

Paddle Pair: No. 31610000 (included)


Optional: RST 91 stand and No. 3233900 adapter



**Counterclockwise  
PUSH**



**Clockwise  
PULL**



**Counterclockwise** rotation pushes material from the top to the bottom, reducing splashing when mixing low-viscosity materials such as paint, glue, filler and leveling compounds.

**Clockwise** rotation pulls material from the bottom to the top, reducing air inclusion and efficiently mixing heavy products such as flooring compound, epoxies, mortars, fiber-filled cements, ceramics, granulates, pastes and putties.