

## **C51 Wet Core Bits**



## C51 Segmented /Double Pointed \* \* \* \* \* PRO V

## Quality Level 5 - Hard Aggregate and Heavy Steel

Faster drilling – The double-pointed segments provide incredibly fast drilling speeds.

Fast seating and reduced vibration — The double-pointed tips penetrate quickly, and hold a straight drilling path to reduce side drag. Reduced vibration improves drilling efficiency and bit life.



2" - 6" are laser welded 6-1/4"> are brazed 16" and above standard with spoke back

Solid or welded backs and special barrel lengths are available upon request.

Wet Bit Specifications	
Bit Diameter	Core Travel
1″ - 14″	14″
16" - 17"	20″
18″ - 19″	22″
20″ - 31″	24″
32" +	36″

Improved cooling and slurry removal – The doublepointed segments increases water flow to reduce heat and removed slurry more efficiently.

Specially formulated segments – Pro V bits contain high concentrations of quality diamonds combined with a special blend of metal powders to deliver maximum performance with lowest drilling costs.

	C51
	Solid
	Back
Dia.	Part No.
<u>2″</u>	D36101
<u>2-1/4″</u>	D36102
<u>2"</u> <u>2-1/4"</u> <u>2 1/2"</u>	D36103
<u>2-3/4″</u>	D36104
<u>2-3/4″</u> 3″	D36105
3-1/4″	D36106
3 1/2"	D36107
<u>3 1/2"</u> 4"	D36108
4-1/4"	D36109
4 1/2"	D36110
5″	D36112
<u>4 1/2"</u> <u>5"</u> <u>5 1/2"</u> <u>6"</u>	D36113
6″	D36115
<u>6-1/4″</u>	D36116
6 1/2"	D36117
7″	D36118
8″	D36119
9″	D36120
10″	D36121
<u>6-1/4"</u> <u>6 1/2"</u> <u>7"</u> <u>8"</u> <u>9"</u> <u>10"</u> <u>12"</u>	D36122
14″ 16″	D36123
16″	D36124
18″	D36125
20″	D36126

1250 NW Main Lees Summit, MO 64086 866-688-1032 877-220-4777 (fax) www.DITEQ.com

