Discover the DITEQ







TG8 TEQ-Grinder

Features:

- Wet or Dry
- Full floating head
- 8" diamond disc
- Lower profile allows the TG8 to grind under toe kicks in cabinets
- Vacuum connection located on the side for easy access. 2" and 3" vacuum port accommodates more vacuums
- Central water feed
- Fold-down handles
- Raise & lower
- Single phase electric motor with thermal overload
- 5.5 hp Honda model or 2 hp Electric
- Convenient location for on/off
- Fully powder coated/zinc plate
- 50' 10 gauge ext. included with electric only

Ideal for:

- Removing paint, epoxy, thinset, urethane coatings and cut back adhesives
- Repairing worn, damaged or spalled concrete
- Leveling uneven or curling slabs
- Grinding hard surfaces, featheredging sidewalks, gutters and similar surfaces
- Grinding high and uneven joints
- Removing excess surface material
- Leveling patches of plastic overlays or grout
- Fast grinding of rough, uneven slab surfaces

TG8 TEQ-GRINDER	GRINDER GRINDER		POLISHER	
Motor	2hp 5.5 Honda		2 hp	
Phase	Single	Gas	Single	
Full Load AMPS @115V	18.4		18.4	
RPM - Disc	2800	2800	Variable 0 - 2800	
Grinding Wheel	8"	8"	8"	
Model	FGE 2L	FGG 5H	FGEP2L	
Weight	130 lbs	120 lbs	130 lbs	
Part No.	G00046*	G00048*	G00047**	
List <i>E</i>	\$3,145	\$3,460	\$3,880	

*Includes 8"grinding disc standard with 10 segments

Standard TG8 TEQ-Grinder Grinding Heads

Diameter & Width	Seg	Grit	Part No.	List
FGG34 8"x3/4"* (std bond)	10	Coarse - 30/40	D91003	\$572
FGP35 8"x3/4"* (std bond)	10	Med - 60/80	D91005	572
FGG36 8"x3/4"* (hard bond)	10	Coarse - 30/40	D91009	572
FGG34 8"x3/4"* (std bond)	5	Coarse - 30/40	D91006	520

*includes rubber isolator 161113



Toll-Free: 866-688-1032 Fax: 877-220-4777 Website: www.DITEQ.com

FGG34

^{**}Includes 8" TEQ-Lok plate and 4- 30 grit 161162