




Husqvarna®



Husqvarna DM 230

Handheld electric core drill with attractive design and functional ergonomics. The motor is designed with an ergonomic pistol grip giving you greater control.

Handheld core drilling up to 4 in. or drilling with stand up to 6 in. Suitable for light applications such as ventilation, plumbing pipes and electrical sockets. DM 230 is an excellent choice for professionals as well as less experienced users.



OVERLOAD PROTECTION

The machine uses pulsation to warn you of an approaching overload. If the load is not reduced the motor will shut off, to prevent overheating. Elgard™ increases productivity and extends product life.



RELIABLE GEARBOX

Watercooled 3 speed gearbox for optimal drilling performance and longer service intervals.



EASY START WITH REDUCED SPEED

Used with starting a hole, speed is reduced by half using the Smart Start® button, which reduces vibration.



DURABLE AND ERGONOMIC DESIGN

Durable and shock-proof, designed to protect the electronics. Easy to carry and install thanks to low weight and ergonomic design.

Features Husqvarna DM 230

- Softstart™ lowers incoming current to reduce amperage when starting the motor.
- Easy to switch between dry and wet drilling
- The machine uses pulsation to warn you of an approaching overload. This increases productivity and extends product life.
- Used with starting a hole, speed is reduced by half using the Smart Start® button, which reduces vibration.
- An electronic current limiter for soft starts with normal fuses. This gives you a smooth start with high productivity and reduces initial load on motor.

TECHNICAL SPECIFICATION

Voltage	230/110 V
Amperage	8/15 A
Power	1850 W
Phases	1
Output RPM	800/1850/3950 rpm
Output RPM at full load	580/1400/2900 rpm
Speeds	3
Water coupling	G 1/4"
Spindle speed full load	580/1400/2900 rpm
Rated output, W	1850/0 W
Rated current, A	8/15 A
Max drill bit diameter, handheld	3 inch
Max drill bit diameter, stand	6 inch
Mounting collar	2.36"
Spindle thread, outer	1 1/4" 7 UNC
Spindle thread, inner	G 1/2" or 5/8" 11 UNC
UNC water coupling	G 1/4"
Weight	15.4 lbs
Sound pressure	90 dB(A)
Sound level	94 dB(A)
Hand arm vibration (Aeq)	2.5 m/s ²
Power rating	1100 W

