



Hydro Ban™



The NEW Industry Standard for Waterproofing Membranes

- No fabric required†
- Flood test in 24 hours†
- Bonds directly to copper, steel, stainless steel and PVC plumbing fixtures†
- Single component
- Exceeds ANSI A118.10 and A118.12
- Applies quickly with a paint roller, brush or trowel
- Lighter color for easier inspection
- Foot traffic in 4 – 6 hours
- Anti-fracture protection of up to 1/8" (3 mm)
- Contains Microban® antimicrobial protection

LATICRETE® Hydro Ban™ is a thin, load-bearing waterproofing and anti-fracture membrane that does not require the use of fabric† in the field, coves or corners. LATICRETE Hydro Ban is a single component self-curing

liquid rubber polymer that forms a flexible, seamless waterproofing membrane that bonds to a wide variety of substrates including copper, steel, stainless steel and PVC plumbing fixtures.

FEATURES	BENEFITS
No Fabric Required†	Prevents leaks without the use of fabric in fields, coves, corners and around pipe penetrations making the application quicker, reducing labor costs.
Single Component	No mixing involved, just open the pail and begin applying.
Meets or Exceeds ANSI A118.10 and A118.12	Meets or exceeds the requirements for both waterproofing and anti-fracture up to 1/8" (3 mm).
Easily Applied with Roller, Brush or Trowel	Easy to apply, no special techniques involved.
Bonds Directly to Copper, Steel, Stainless Steel and PVC plumbing fixtures	No need to use multiple materials around pipe penetrations or drains, one product does it all.
Lighter Color	Allows you to detect the presence of missed areas or foreign particles from the work surroundings.
Flood Test in 24 Hours†	When fully cured at 70°F (21°C) or above to an olive green color, LATICRETE® Hydro Ban™ can be flood tested in 24 hours.
Foot Traffic in 4 – 6 Hours	Cures quickly allowing for a second coat or tile application.
Contains Microban®	Protects substrate from stain-causing mold and mildew growth with antimicrobial product protection.

Uses

- Interior and Exterior
- Swimming Pools, Fountains and Water Features
- Shower Pans, Stalls and Tub Surrounds
- Bathrooms and Laundries (Industrial, Commercial and Residential)
- Spas, Steam Rooms and Hot Tubs
- Kitchens and Food Processing Areas
- Terraces and Balconies over Unoccupied Spaces
- Counter Tops
- Facades

Suitable Substrates

- Concrete
- Cement Mortar Beds
- Exterior Glue Plywood*
- Gypsum Wallboard*
- Ceramic Tile and Stone**
- Cement Terrazzo**
- Cement Plaster
- Concrete and Brick Masonry
- Cement Backer Board***

*Interior application only.

**If skim coated with a LATICRETE® latex thin-set mortar.

***Consult cement backer board manufacturer for specific installation recommendations and to verify acceptability for exterior use.

Information

† See Data Sheets 663.0 and 663.5 for complete details.

Packaging

COMMERCIAL UNIT

5 gallon (18.9 ℓ) pail liquid; 36 units per pallet.

FULL UNIT

2 gallon (7.6 ℓ) pail liquid; 80 units per pallet.

MINI UNIT

4 x 1 gallon (3.8 ℓ) pails of liquid packed in a carton; 30 cartons per pallet.

Approximate Coverage

COMMERCIAL UNIT: 250 ft² (23.2 m²). Part number: 9255-0005-2.

FULL UNIT: 100 ft² (9.3 m²). Part number: 9255-0002-2.

MINI UNIT: 50 ft² (4.7 m²). Part number: 9255-0401-2.

LATICRETE INTERNATIONAL, INC.

One LATICRETE Park North
Bethany, CT 06524-3423 USA

800.243.4788

203.393.0010

www.laticrete.com

©2007 LATICRETE INTERNATIONAL, INC.
LATICRETE, LATAPOXY and the  logo are Registered Trademarks of LATICRETE International, Inc.
Microban is a registered trademark of Microban Products Company.