GROUT RELEASE

PRW200

ALL ABSORBENT NATURAL STONE, QUARRY TILE, TERRACOTTA





- WATER-BASED PROTECTION AGAINST GROUT AND MORTAR STAINS.
- REDUCES DRYING TIME AND EASES GROUT CLEANUP.

Coverage: 1 QT (0.95 L)

Natural stone > 108-215 sq.ft. (10-20 m²) Terracotta > 75-108 sq.ft. (7-10 m²)

Coverage rates are indicative and per coat.

Packaging:

1 QT (946 ml) 5 plastic bottles per box

WHAT IT'S FOR

- Protects the surface against grout, construction dirt and mortar stains.
- Makes grout cleanup easy.
- Reduces grout drying time.
- Forms an invisible, protective barrier resistant to moisture and stains while allowing water vapor to escape.
- Ideal for absorbent materials: natural and reconstructed stone, quarry tile and terracotta.

ADVANTAGES

- Eco-friendly: water-based.
- Does not alter the material's natural color and finish.
- Makes post-construction cleaning simple, so that the appropriate sealer can be easily applied.
- VOC free: contributes towards LEED credits.
- PFOA free: non carcinogenic.

HOW TO USE IT

Ready to use, no dilution necessary.

Make sure the surface to be treated is completely free of dust. Apply an even coat of **PRW200** using a paintbrush or lambswool applicator pad, avoiding surface pooling. Ensure the product also covers the edges of the installed material. The surface may be grouted 4 hours after the application of grout release **PRW200**. After the grout is cured, clean the surface with an appropriate cleaner for the material. After cleaning, apply a protective sealer. The product is not recommended for ceramic tile, polished porcelain or nonporous materials.

Caution: Before full application, test **PRW200** on a small, inconspicuous area of the surface or loose sample to check for any changes in color. Do not apply the product outdoors if rain is in the forecast.

FILA. Because It Works.

Fila Chemicals USA, Corp. Miami, FL 33172 tel +1-305-513-0708 filausa@filasolutions.com

TOLL FREE 1-844-FILA123





Recommended by over

200 INTERNATIONAL TOP BRANDS
manufacturers of materials for floors and wall coverings