





AVAILABLE SPONGES




ACCESSORIES



PACKAGE



TECHNICAL CHARACTERISTICS



- Electro-sponge for cleaning grout (cement based or epoxy resin) from floors: Terracotta, porcelain, double-fired and single-fired tiles, marble, clinker, porphyry, natural stone, quarry tile, treaded tile, etc. during the grouting phase.
- Does not pull grout from the joints. Easy handling, suitable for use even in small areas.
- Performance: 100 sm/h for medium difficulty surfaces (800 - 1500 s.f. per hour in general).
- Sponge rollers can last from 150 to 2000 sm (1600 - 21000 s.f.).
- Moisture level of the sponge roller is adjustable via the pressure adjustment lever. Easy-to-use pressure adjustment lever also adjusts the front wheels.

- Easy-to-replace sponge roller thanks to the magnetic "quick clutch" system.
- Water is fed to the roller via a foam-reducing belt (no pump to clog up).
- The handle folds down for transport or storage, and its ergonomic design are fully adjustable for height and angle according to the user(s) needs.
- Die cast aluminum body reduces weight while increasing overall strength.
- Easy-to-remove water-tank (15 liters, 4 gal.) is made of impact resistant plastic to reduce breakage.
- Standard with: sponge roller for cement based grout, anti-foaming liquid, user and maintenance manual.

MODEL SPECIFICATIONS

Part No.	Barcode	Box	Lightning Bolt	M	Motor	Motor	Sponge	Sponge
399 ADV	8024648004529	1	230 V 50/60 Hz	Single-phase	0,16 HP / 0,12 kW	2800/3360	Sponge "Avana"	21 / 25
399 ADV GB	8024648009685	1	110 V 50 Hz	Single-phase	0,16 HP / 0,12 kW	2800		21
399 ADV USA	8024648009692	1	110 V 60 Hz	Single-phase	0,16 HP / 0,12 kW	3360		25

DIMENSIONS AND WEIGHT

Part No.	Dimensions	Dimensions	Weight	Weight	Dimensions	Dimensions	Weight	Weight
BERTA ADV	65x55xh 50 cm	25 3/8" x 21 5/8" x h 20"	29 Kg	64 lbs	73x60xh 55 cm	29" x 23 5/8" x h 21 5/8"	32 Kg	70 lbs




ELECTROSPONGES

SPONGE ROLLERS AND ANTIFOAM LIQUID

MADE IN ITALY



380RULLO



AVANA



380RULSWE



SWEEPEX



380RULEPO



CELLULOSA



380ANTISC400

380ANTISC

PACKAGE



CARTON BOX

- Sponge roller "Avana" (brown) for cement based grout.
- Sponge roller "Sweepex" (soft yellow) high absorption for cement based grout.
- Sponge roller "Cellulosa" (dense yellow) for epoxy resin based grout.

- Antifoaming liquid for use on heavy latex modified grouts to avoid foaming.
- Dosage 5 ml x liter of water (1/2 oz. - 1 oz. per Gallon)
- Available in 100 gr and 400 gr (3.5 and 14 oz) bottles.

SPONGE ROLLER

Part No.			Sponge	Roller dimension							
380RULLO	8024648004925	4	Havana	Ø 295x400 mm	Ø 11 5/8" x 15 3/4"	1,9 Kg	4.2 lbs	75x60xh 40 cm	29"x23"xh 15"	10,6 Kg	23.4 lbs
380RULSWE	8024648003263	4	Sweepex			2 Kg	4.4 lbs			11 Kg	24 lbs
380RULEPO	8024648003270	4	Celulose			2,3 Kg	5 lbs			12,2 Kg	27 lbs

ANTIFOAM

Part No.										
380ANTISC400	8024648011800	5	400 gr	14 oz	470 gr	16.6 oz	20x20xh 15 cm	8"x8"xh 6"	3 Kg	6.6 lbs
380ANTISC	8024648003256	10	100 gr	3.5 oz	120 gr	4.2 oz	27x10xh 15 cm	10 5/8"x4"xh 6"	1,3 Kg	2.9 lbs

ELECTROSPONGES