

USG DUROCK® Brand
Cement Board with EdgeGuard™

SMOOTH SIDE MASTIC, ROUGH SIDE MORTAR

891 12/21/19 02:54 INSTRUCTIONS USG.COM

USG
Cement

SMOOTH

19 02:5

EdgeGuard™

EdgeGuard™

EdgeGuard™

EdgeGuard™

EdgeGuard™

EdgeGuard™

EdgeGuard™

USG DUROCK™ BRAND UNCOUPLING MAT

- Provides uncoupling, waterproofing and vapor management of the substrate
- Lighter, thinner alternative to traditional tile underlayment panels
- Low density core helps keep the membrane flat during installation
- Fast track; tile installation can begin immediately after the membrane is installed
- Approved for use with modified and unmodified mortars

USG DUROCK™ BRAND UNCOUPLING MAT

A waterproof underlayment membrane that helps suppress the transfer of lateral movement in a subfloor to preserve the integrity of the tile installation.

DESCRIPTION

USG Durock™ Brand Uncoupling Mat is a lightweight, high performance crack isolation, waterproofing and vapor management underlayment membrane for use with porcelain, ceramic, and natural stone tile in both residential and commercial applications. When exposed to stresses from in-plane lateral movement of the substrate, the USG Durock™ Uncoupling Mat absorbs and prevents the transfer of those stresses (up to 1/8"), helping to preserve the integrity of the tile installation. For applications where waterproofing is required, treat joints with USG Durock™ Brand Waterproofing Membrane Band.

Unlike most other mats, the USG Durock™ Uncoupling Mat features a low-density polyethylene (LDPE) core to reduce roll-back memory during installation. The LDPE core also provides the mat with increased flexibility making it easier to handle, cut and install. The reinforced fleece backing helps to provide a secure mechanical bond to the substrate while the combination of non-woven fabric and unique dimple design allow the installer to fill in the cavities with mortar with minimal effort.

Suitable substrates include concrete*, green concrete, exterior-grade plywood, tile backerboard (like USG Durock® Brand Cement Board or USG Fiberock® Brand Tile Underlayment), gypsum underlayment* (like USG Levelrock® Brand Floor Underlayments), and more.

* Follow manufacturer's recommendation regarding priming and/or special surface preparation before installing USG Durock™ Uncoupling Mat.

SIZE AND PACKAGING

USG Durock™ Brand Uncoupling Mat		USG Durock™ Waterproofing Membrane Band	
Item Number	170007	Item Number	170149
Roll Size	43" x 98' (1.1m x 30m)	Roll Size	5" x 50' (12.7 cm x 15 m)
Coverage	351 sq. ft.	Coverage	20.8 sq. ft.
Quantity per Pallet	9 rolls		

TECHNICAL DATA

Property	ANSI / ASTM Test	USG Durock™ Uncoupling Mat
Thickness	n/a	1/8" (3mm)
Fungus and microorganism resistance	ANSI A118.10	No mold growth
Seam strength	ANSI A118.10 / ASTM D751	>8 lbs./in.
Breaking strength	ANSI A118.10 / ASTM D751	>170 psi
Dimensional stability	ANSI A118.10 / ASTM D1204	<0.7%
Waterproofness	ANSI A118.10 / ASTM D4068	Pass
Shear strength to ceramic tile and cement mortar	ANSI A118.10 / ASTM C482	>50 psi
Point load	ANSI A118.12	>1000 lbs.
Crack resistance	ANSI A118.12	No failure up to 1/8 in. crack opening
Robinson Service Rating	ASTM C627	Wood substrate, 24" o.c. - Heavy Concrete slab - Extra Heavy
Recycled Content	n/a	up to 70%



CB906-USA-ENG/10-20

© 2020 USG Corporation and/or its affiliates.
All rights reserved.
Printed in U.S.A.

Manufactured by or for
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

PRODUCT INFORMATION

See usg.com for the most up-to-date product information.
Product safety information: 800 507-8899 or usg.com.
Customer Service: 800 USG.4YOU (874-4968).

KEEP OUT OF REACH OF CHILDREN.

NOTE

Products described here may not be available in all geographic markets. The information in this document is subject to change without notice. USG and/or its affiliates assume no responsibility for any errors that may inadvertently appear in this document. Consult your USG sales office or representative for information.

NOTICE

We shall not be liable for consequential, incidental or special damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods or a refund of the purchase price, at USG's option. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

TRADEMARKS

The trademarks USG, LSP, FIBEROCK, LEVELROCK, DUROCK, IT'S YOUR WORLD.BUILD IT., the USG logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.