



## Safety Data Sheet – ULTRA X GUARD

Version 1.0 / 2018

Alpinebay Inc  
1668 El Pinal Drive  
Stockton, CA 95205  
Emergency Phone: 1-209-462-1818

### **Section I: Product Identification**

Trade Name: Ultra X Guard Waterproof Membrane  
Chemical Name: None  
Chemical Family: Mixture

### **Section II: Component Information**

Carcinogenicity: IARC (Not Regulated), NTP (Not Regulated), OSHA (Not Regulated)

### **Section III: Physical Data**

Appearance and Odor: Gold liquid paste with a mild odor  
Boiling Point: N/A  
Melting Point: N/A  
Vapor Pressure: N/A  
Vapor Density: Heavier than air  
Specific Gravity: >1  
Solubility: Dilutable  
Evaporation Rate: Slower than ether

### **Section IV: Fire and Explosion Data**

Flash Point: Noncombustible  
Lower Explosion Limits: N/A  
Auto-ignition Temperature: N/A  
Potential Hazards: Material can splatter above 212° F/100° C, polymer film can burn.  
Extinguishing Media: Use extinguishing media appropriate for the surrounding fire.  
Personal Protection: Wear self-contained breathing apparatus and full protective gear.

### **Section V: Health Hazard Data**

ACGIH TLV (OSHAPEL): Mixture (See Section II)  
Primary Routes of Exposure: Inhalation, skin, and eye contact  
Inhalation: May cause respiratory tract irritation  
Eye contact: Direct contact with eyes can cause eye irritation  
Skin contact: Prolonged or repeated skin contact can cause skin irritation, such as drying, redness, and cracking of the skin.  
Ingestion: If swallowed, give at least 2 glasses of water to drink, do not induce vomiting unless directed by a physician. Consult a physician if irritation persists. Never give anything by mouth to an unconscious person.

### **Section VI: Reactivity Data**

Stability: Stable. Avoid temperatures above 350° F/177° C, as this may lead to polymer decomposition. Thermal decomposition is dependent on time and temperature.  
Incompatibility: No known incompatible materials  
Hazardous Decomposition: Thermal decomposition may yield monomer vapors and oxides of carbon.  
Hazardous Polymerization: Will not occur  
Storage: Keep tightly closed and stored in a cool place at 35- 120° F. Keep away from freezing and sunlight.

### **Section VII: Spill or Leak Procedures**

Personal Protection: See Section V Health Hazard Data and Section VIII Special Protection. Keep spectators away. The floor may become slippery, exercise caution to prevent falls. Clean immediately with inert materials. Transfer liquids and solid drying material to suitable containers for recovery or disposal.  
Waste Disposal: Dispose of in accordance with applicable federal, state, and local regulations. Keep spills and runoff out of drains, municipal sewer, and open bodies of water.

### **Section VIII: Special Protection Information**

Respiratory Protection: None required for normal use of this product  
Eye Protection: Use chemical splash goggles (ANSI 287.1 or approved equivalent).  
Hand Protection: Rubber or plastic gloves  
Protective Equipment: Local ventilation, full-flow eyewash station for emergency wash

### **Section IX: Special Precautions and Information**

US DOT Hazard Class: Not Regulated  
NTP: Health 0, Flammability 0, Reactivity 0  
HMIS: Health 0, Flammability 0, Reactivity 0  
(Health rating applies only to acute effects as defined by the National Paint and Coating Association)

This information is furnished without warranty, representation, inducement, or license of any kind, except that it is accurate to the best of Alpinebay Inc's knowledge or is obtained from sources believed to be accurate. Alpinebay Inc. does not assume any legal responsibility for its use or reliance upon the same. Customers are encouraged to conduct their own tests. Before using any product, read its label.

Contact Information:  
Tel: +1 (209) 462 1818  
Fax: +1 (209) 462 8888  
Email: [info@alpinebay.com](mailto:info@alpinebay.com)

